

**PRODUCT :**      **TFT TOUCH MODULE****MODULE NO. :**    **WKS70WSV004-WCT****SUPPLIER:**        **WKS Technology Co., LTD****DATE:**              **Sep 28, 2017**

# ***SPECIFICATION***

*Revision: 0.0****WKS70WSV004-WCT****This module uses ROHS material*

*This specification may change without prior notice in order to improve performance or quality. Please contact WKS R&D department for updated specification and product status before design for this product or release of this order.*

<b><i>WRITTEN BY</i></b>	<b><i>CHECKED BY</i></b>	<b><i>APPROVED BY</i></b>
<i>Jason</i>	<i>Eric</i>	<i>Henry</i>




## ***CONTENTS***

- 1、GENERAL INFORMATION***
- 2、EXTERNAL DIMENSIONS***
- 3、ABSOLUTE MAXIMUM RATINGS***
- 4、ELECTRICAL CHARACTERISTICS***
- 5、BACKLIGHT CHARACTERISTICS***
- 6、CTP CHARACTERISTICS***
- 7、ELECTRO-OPTICAL CHARACTERISTICS***
- 8、INTERFACE DESCRIPTION***
- 9、INPUT TIMING***
- 10、RELIABILITY TEST CONDITIONS***
- 11、INSPECTION CRITERION***

## 1、GENERAL INFORMATION

<i>Item of general information</i>	<i>Contents</i>		<i>Unit</i>
<i>LCD Display Size (Diagonal)</i>	7.0		<i>inch</i>
<i>Module Structure</i>	<i>LCD Display + CTP Touch + PCB</i>		-
<i>LCD Display Type</i>	<i>TFT/TRANSMISSIVE</i>		-
<i>LCD Display Mode</i>	<i>Normally White</i>		-
<i>Recommended Viewing Direction</i>	12		<i>o'clock</i>
<i>Gray inversion Direction</i>	6		<i>o'clock</i>
<i>Module size (W×H×T)</i>	185.77×109.71×8.45		<i>mm</i>
<i>Active area (W×H)</i>	154.21×85.92		<i>mm</i>
<i>Number of pixels (Resolution)</i>	1024RGB×600		<i>pixel</i>
<i>Pixel pitch (W×H)</i>	0.1506×0.1432		<i>mm</i>
<i>Module Interface Type</i>	<i>LCD</i>	<i>LVDS interface</i>	-
	<i>CTP</i>	<i>USB interface</i>	-
<i>Module Input voltage</i>	5.0V		<i>V</i>
<i>Module Power consumption</i>	-		<i>mW</i>
<i>Color Numbers</i>	16.7M		-
<i>Backlight Type</i>	<i>White LED</i>		-

## 2. EXTERNAL DIMENSIONS




### 3、ABSOLUTE MAXIMUM RATINGS

Parameter of absolute maximum ratings	Symbol	Min	Max	Unit
Operating temperature	$T_{op}$	-20	70	°C
Storage temperature	$T_{st}$	-30	80	°C
Humidity	RH	-	90%(Max 60°C)	RH

Note: Absolute maximum ratings means the product can withstand short-term, not more than 120 hours. If the product is a long time to withstand these conditions, the life time would be shorter.

### 4、ELECTRICAL CHARACTERISTICS(DC CHARACTERISTICS)

Parameter of DC characteristics	Symbol	Min.	Typ.	Max.	Unit
LVDS Differential input high threshold voltage	$R_x V_{TH}$	-	-	+0.1	V
LVDS Differential input low threshold voltage	$R_x V_{TL}$	-0.1	-	-	V
LVDS Differential input common mode voltage	$R_x V_{CM}$	$ V_{ID} /2$		$2.4 -  V_{ID} /2$	V
LVDS Differential input voltage	$ V_{ID} $	0.2	-	0.6	V




## 5、BACKLIGHT CHARACTERISTICS

<i>Item of backlight characteristics</i>	<i>Symbol</i>	<i>Min.</i>	<i>Typ.</i>	<i>Max.</i>	<i>Unit</i>	<i>Remark</i>
<i>Forward Voltage</i>	<i>V<sub>f</sub></i>	8.7	9.3	9.9	<i>V</i>	<i>Note1</i>
<i>Forward Current</i>	<i>I<sub>f</sub></i>	-	180	-	<i>mA</i>	-
<i>Number of LED</i>	-	-	3*9=27	-	<i>Piece</i>	-
<i>LED Connection mode</i>	<i>P/S</i>	-	<i>Serial/Parallel</i>	-	-	-
<i>Lifetime of LED</i>	-	-	10000	-	<i>hour</i>	<i>Note2</i>

Note:

- Note1: The LED Supply Voltage is defined by the number of LED at  $T_a=25^{\circ}\text{C}$  and  $I_f=180\text{mA}$ .
- Note2: The LED lifetime define as the estimated time to 80% degradation of initial luminous. The LED lifetime could be decreased if operating  $I_f$  is larger than 180mA.
- Backlight control via the BL\_PWM pin.
- Backlight circuit:



## 6、CTP CHARACTERISTICS

<i>Item of CTP characteristics</i>	<i>Specification</i>	<i>Unit</i>	<i>Remark</i>
<i>Panel Type</i>	<i>Glass Cover + Glass Sensor</i>	-	-
<i>Resolution</i>	<i>1024 × 600</i>	<i>pixel</i>	-
<i>Surface Hardness</i>	<i>≥6H</i>	-	-
<i>Transparency</i>	<i>&gt;82%</i>	-	-
<i>Driver IC</i>	-	-	-
<i>Interface Type</i>	<i>USB</i>	-	-
<i>Support Points</i>	<i>5</i>	-	-
<i>Sampling Rate</i>	<i>20~100</i>	<i>Hz</i>	-
<i>Supply voltage</i>	<i>3.3</i>	<i>V</i>	-



## 7、ELECTRO-OPTICAL CHARACTERISTICS

Item of electro-optical characteristics		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark	Note
Response time		Tr+Tf	$\theta=0$ $\phi=0$ $Ta=25^{\circ}C$	-	25	50	ms	FIG 1.	4
Contrast Ratio		CR		-	400	-	-	FIG 2.	1
Luminance uniformity		$\delta WHITE$		-	80	-	%	FIG 2.	3
Surface Luminance		Lv		-	250	-	cd/m2	FIG 2.	2
CIE (x, y) chromaticity	White	White x	$\theta=0$	-	0.31	-	-	FIG 2.	5
		White y	$\phi=0$ $Ta=25^{\circ}C$	-	0.33	-			
Viewing angle range	$\phi=90(12\text{ o'clock})$		$CR \geq 10$	-	70	-	deg	FIG 3.	6
	$\phi=270(6\text{ o'clock})$			-	75	-	deg		
	$\phi=0(3\text{ o'clock})$			-	75	-	deg		
	$\phi=180(9\text{ o'clock})$			-	75	-	deg		
NTSC ratio		-	-	-	50	-	%	-	-

**Note 1.** Contrast Ratio(CR) is defined mathematically by the following formula. For more information see FIG 2.:

$$\text{Contrast Ratio(CR)} = \frac{\text{Average Surface Luminance with all white pixels(P1,P2,P3,P4,P5,P6,P7,P8,P9)}}{\text{Average Surface Luminance with all black pixels(P1,P2,P3,P4,P5,P6,P7,P8,P9)}}$$

**Note 2.** Surface luminance is the LCD surface from the surface with all pixels displaying white. For more information see FIG 2.

$$L_v = \text{Average Surface Luminance with all white pixels (P1,P2,P3,P4,P5,P6,P7,P8,P9)}$$

**Note 3.** The uniformity in surface luminance ( $\delta WHITE$ ) is determined by measuring luminance at each test position 1 through 9, and then dividing the maximum luminance of 9 points luminance by minimum luminance of 9 points luminance. For more information see FIG 2.

$$\delta_{\text{WHITE}} = \frac{\text{Minimum Surface Luminance with all white pixels (P1, P2, P3, P4, P5, P6, P7, P8, P9)}}{\text{Maximum Surface Luminance with all white pixels (P1, P2, P3, P4, P5, P6, P7, P8, P9)}}$$

**Note 4.** Response time is the time required for the display to transition from White to black(Rise Time,  $T_r$ ) and from black to white(Decay Time,  $T_f$ ). For additional information see FIG 1.


**Note 5.** CIE (x, y) chromaticity ,The x,y value is determined by screen active area position 5. For more information see FIG 2.

**Note 6.** Viewing angle is the angle at which the contrast ratio is greater than a specific value. For TFT module, the specific value of contrast ratio is 10.The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG 3.

**Note 7.** For Viewing angle and response time testing, the testing data is base on Autronic-Melchers's ConoScope. Series Instruments. For contrast ratio, Surface Luminance, Luminance uniformity and CIE, the testing data is base on BM-7 photo detector.

**Note 8.** For TN type TFT transmissive module, Gray scale reverse occurs in the direction of panel viewing angle.

**FIG.1. The definition of Response Time**



**FIG.2. Measuring method for Contrast ratio, surface luminance, Luminance uniformity,**


### CIE (x , y) chromaticity

$A : H/6 ;$


$B : V/6 ;$

$H, V : \text{Active Area(AA) size}$

Measurement instrument: BM-7; Light spot size=5mm, 350mm distance from the LCD surface to detector lens.



**FIG.3. The definition of viewing angle**



## 8、INTERFACE DESCRIPTION

**Connector: DF19G-20P-1H**


NO.	Symbol	I/O	DESCRIPTION	Remark
1~2	5V	P	Module Power supply (5V Typ.)	
3~4	GND	P	Ground	
5	RX0-	I	-LVDS Differential Data Input	R0~R5,G0
6	RX0+	I	+LVDS Differential Data Input	
7	GND	P	Ground	
8	RX1-	I	-LVDS Differential Data Input	G1~G5,B0,B1
9	RX1+	I	+LVDS Differential Data Input	
10	GND	P	Ground	
11	RX2-	I	-LVDS Differential Data Input	B2~B5,HS,VS,DE
12	RX2+	I	+LVDS Differential Data Input	
13	GND	P	Ground	
14	RXCLK-	I	-LVDS Differential Clock Input	LVDS CLK
15	RXCLK+	I	+LVDS Differential Clock Input	
16	GND	P	Ground	
17	RX3-	I	-LVDS Differential Data Input	R6,R7,G6,G7,B6,B7
18	RX3+	I	+LVDS Differential Data Input	
19	GND	P	Ground	
20	BL_PWM	I	Backlight control signal	

## 9、INPUT TIMING

### *HV mode input Timing table*

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
DCLK frequency@ Frame rate=60Hz	DCLK	44.9	51.2	63	MHz
Horizontal display area	thd	1024			DCLK
1 Horizontal Line	th	1200	1344	1400	DCLK
HSYNC pulse width	thpw	1	-	140	DCLK
HSYNC Blanking	thb	160	160	160	DCLK
HSYNC Front Porch	thfp	16	160	216	DCLK
Vertical display area	tvd	600			H
VSYNC period time	tv	624	635	750	H
VSYNC pulse width	tpw	1	-	20	H
VSYNC Blanking	tvb	23	23	23	H
VSYNC Front Porch	tvfp	1	12	127	H

### *LVDS Data Input Format*



**10、RELIABILITY TEST CONDITIONS**

No.	Test Item	Test Condition
1	High Temperature Storage	80°C/120 hours
2	Low Temperature Storage	-30°C/120 hours
3	High Temperature Operating	70°C/120 hours
4	Low Temperature Operating	-20°C/120 hours
5	Temperature Cycle Storage	-20°C(30min.)~25(5min.)~70°C(30min.)×10cycles

**A、Inspection after test:**

Inspection after 2~4 hours storage at room temperature, the sample shall be free from defects:

- Air bubble in the LCD;
- Sealleak;
- Non-display;
- Missing segments;
- Glass crack;
- Current is twice higher than initial value.

**B、Remark:**

- The test samples should be applied to only one test item.
- Sample size for each test item is 5~10pcs.
- Failure Judgment Criterion: Basic Specification, Electrical Characteristic, Mechanical Characteristic, Optical Characteristic.

## **11、INSPECTION CRITERION**

*This specification is made to be used as the standard of acceptance/rejection criteria for TFT-LCD/IPS TFT-LCD module product, and this specification is applicable only in the case that the size of module equal to or exceed than 3.5 inch.*

### **11.1 Sample plan**

*Sampling plan according to GB/T2828.1-2003/ISO 2859-1: 1999 and ANSI/ASQC*

*Z1.4-1993,normal level 2 and based on:*

*Major defect: AQL 0.65*


*Minor defect: AQL 1.5*

### **11.2 Inspection condition**

*Viewing distance for cosmetic inspection is about 30cm with bare eyes, and under an environment of 20~40W light intensity, all directions for inspecting the sample should be within 45° against perpendicular line. (Normal temperature 20~25 °C and normal humidity 60 ±15%RH)*

### **11.3 Definition of Inspection Item.**

*A、Definition of inspection zone in LCD.*



*Zone A: character/Digit area*

*Zone B: viewing area except Zone A (Zone A + Zone B=minimum Viewing area)*

*Zone C: Outside viewing area (invisible area after assembly in customer's product)*

*Fig.1 Inspection zones in an LCD*

*Note: As a general rule, visual defects in Zone C are permissible, when it is no trouble for quality and assembly of customer's product.*

### **B、Definition of some visual defect**

<i>Bright dot</i>	<i>Because of losing all or part function, bad pixel dots appear bright and the size is more than 50% of one dot in which LCD panel is displaying under black pattern.</i>
<i>Dark dot</i>	<i>Dots appear dark and unchanged in size in which LCD panel is displaying under pure red, green, blue picture, or pure whiter picture.</i>




## **11.4 Major Defect**

<b>Item No.</b>	<b>Items to be inspected</b>	<b>Inspection standard</b>	<b>Classification of defects</b>
1	Functional defects	1) No display 2) Display abnormally 3) Missing vertical, horizontal segment 4) Short circuit 5) Excess power consumption 6) Backlight no lighting, flickering and abnormal lighting	major
2	Missing	Missing component	
3	Outline dimension	Overall outline dimension beyond the drawing is not allowed	







4	Polarizer defect	5.4.1 Polarizer Position (i) Shifting in position should not exceed the glass outline dimension. (ii) Incomplete covering of the viewing area due to shifting is not allowed.	Minor																														
		5.4.2 Dirt on polarizer Dirt which can be wiped easily should be acceptable.																															
		5.4.3 Polarizer Dent & Air bubble																															
		<table><tr><th colspan="2" rowspan="2">Zone  Size(mm)</th><th colspan="3">Acceptable Qty</th><th rowspan="3">C</th></tr><tr><th colspan="3">A+B</th></tr><tr><th colspan="2"></th><th>3.5''~7''</th><th>7~10.1''</th><th>&gt;10.1''</th></tr><tr><td colspan="2"><math>\Phi \leq 0.2</math></td><td>Acceptable</td><td>Acceptable</td><td>Acceptable</td><td rowspan="3">Acceptable</td></tr><tr><td colspan="2"><math>0.2 &lt; \Phi \leq 0.5</math></td><td>4</td><td>5</td><td>6</td></tr><tr><td colspan="2"><math>\Phi &gt; 0.5</math></td><td>0</td><td>0</td><td>0</td></tr></table>		Zone  Size(mm)		Acceptable Qty			C	A+B					3.5''~7''	7~10.1''	>10.1''	$\Phi \leq 0.2$		Acceptable	Acceptable	Acceptable	Acceptable	$0.2 < \Phi \leq 0.5$		4	5	6	$\Phi > 0.5$		0	0	0
		Zone  Size(mm)				Acceptable Qty				C																							
				A+B																													
				3.5''~7''	7~10.1''	>10.1''																											
		$\Phi \leq 0.2$		Acceptable	Acceptable	Acceptable	Acceptable																										
		$0.2 < \Phi \leq 0.5$		4	5	6																											
		$\Phi > 0.5$		0	0	0																											
5.4.4 Polarizer scratch (i) If the polarizer scratch can be seen after cover assembling or in the operating condition, judge by the linear defect of 5.3. (ii) If the polarizer scratch can be seen only in non-operating condition or some special angle, judge by the following:																																	
<table><tr><th colspan="2" rowspan="2">Zone  Size (mm)</th><th colspan="3">Acceptable Qty</th><th rowspan="3">C</th></tr><tr><th colspan="3">A+B</th></tr><tr><th>Length</th><th>Width</th><th>3.5''~7''</th><th>7~10.1''</th><th>&gt;10.1''</th></tr><tr><td>Ignore</td><td><math>W \leq 0.05</math></td><td>Acceptable</td><td>Acceptable</td><td>Acceptable</td><td rowspan="3">Acceptable</td></tr><tr><td><math>1.0 &lt; L \leq 5.0</math></td><td><math>0.05 &lt; W \leq 0.20</math></td><td>4</td><td>5</td><td>6</td></tr><tr><td><math>L &gt; 5.0</math></td><td><math>W &gt; 0.2</math></td><td>0</td><td>0</td><td>0</td></tr></table>	Zone  Size (mm)		Acceptable Qty			C	A+B			Length	Width	3.5''~7''	7~10.1''	>10.1''	Ignore	$W \leq 0.05$	Acceptable	Acceptable	Acceptable	Acceptable	$1.0 < L \leq 5.0$	$0.05 < W \leq 0.20$	4	5	6	$L > 5.0$	$W > 0.2$	0	0	0			
Zone  Size (mm)			Acceptable Qty				C																										
		A+B																															
Length	Width	3.5''~7''	7~10.1''	>10.1''																													
Ignore	$W \leq 0.05$	Acceptable	Acceptable	Acceptable	Acceptable																												
$1.0 < L \leq 5.0$	$0.05 < W \leq 0.20$	4	5	6																													
$L > 5.0$	$W > 0.2$	0	0	0																													
5	MURA	Using 3% ND filter, it's NG if it can be seen in R,G,B picture.	Minor																														
	White/Black dot (MURA)	Visible under: ND3%; $D \leq 0.15\text{mm}$ , Acceptable; $0.15\text{mm} < D \leq 0.5\text{mm}$ , $N \leq 4$ ; $D > 0.5\text{mm}$ , Not allowable.																															

6	Glass defect	<div>(i) Crack Cracks are not allowed.</div> <div></div>	Minor								
		<div>(ii) TFT chips on corner</div> <div></div> <table><tr><td>X</td><td>Y</td><td>Z</td><td>Acceptable</td></tr><tr><td>≤3.0</td><td>≤3.0</td><td>Not more than the thickness of glass</td><td>N≤3</td></tr></table> <div>Chips on the corner of terminal shall not be allowed to extend into the ITO pad or expose perimeter seal.</div>	X	Y	Z	Acceptable	≤3.0	≤3.0	Not more than the thickness of glass	N≤3	Minor
		X	Y	Z	Acceptable						
≤3.0	≤3.0	Not more than the thickness of glass	N≤3								
<div>(iii) Usual surface crack</div> <div></div> <table><tr><td>X</td><td>Y</td><td>Z</td><td>Acceptable</td></tr><tr><td>≤1.5</td><td>≤1.5</td><td>Not more than the thickness of glass</td><td>N≤4</td></tr></table> <div>It is only applicable to the upper glass of LCD.</div>	X	Y	Z	Acceptable	≤1.5	≤1.5	Not more than the thickness of glass	N≤4	Minor		
X	Y	Z	Acceptable								
≤1.5	≤1.5	Not more than the thickness of glass	N≤4								

## 11.6 Module Cosmetic Criteria

Item No.	Items to be inspected	Inspection Standard	Classification of defects
1	Difference in Spec.	Not allowable	Major
2	Pattern peeling	No substrate pattern peeling and floating	Major
3	Soldering defects	No soldering missing	Major
		No soldering bridge	Major
		No cold soldering	Minor
4	Resist flaw on PCB	Visible copper foil ( $\Phi 0.5$ mm or more) on substrate pattern is not allowed	Minor
5	FPC gold finger	No dirt, breaking, oxidation lead to black	Major
6	Backlight plastic frame	No deformation, crack, breaking, backlight positioning column breaking, obvious nick.	Minor
7	Marking printing effect	No dark marking, incomplete, deformation lead to unable to judge	Minor
8	Accretion of metallic Foreign matter	No accretion of metallic foreign matter (Not exceed $\Phi 0.2$ mm)	Minor
9	Stain	No stain to spoil cosmetic badly	Minor
10	Plate discoloring	No plate fading, rusting and discoloring	Minor
11	1. Lead parts	a. Soldering side of PCB Solder to form a 'Filet' all around the lead. Solder should not hide the lead form perfectly.	Minor
		b. Components side(In case of 'Through Hole PCB') Solder to reach the Components side of PCB.	Minor
	2. Flat packages	Either 'Toe'(A) or 'Seal'(B) of the lead to be covered by "Filet". Lead form to be assume over Solder. 	Minor
	3. Chips	$(3/2) H \geq h \geq (1/2) H$ 	Minor
	4. Solder ball/Solder splash	a. The spacing between solder ball and the conductor or solder pad $h \geq 0.13$ mm. The diameter of solder ball $d \leq 0.15$ mm.	Minor
		b. The quantity of solder balls or solder splashes isn't beyond 5 in 600 mm <sup>2</sup> .	Minor
		c. Solder balls/Solder splashes do not violate minimum electrical clearance.	Major